

SpiderFit

Frameless Glass Fittings

The Austvision SpiderFit provides a full range of cast 316 marine grade stainless steel spider fittings used in frameless glass point supported glass systems.

SpiderFit provides a flexible connection between the structural glass and the supporting system, and the Spider Fittings can be assembled with a range of glass connectors.

SpiderFit Range

Heavy duty:	445 series – 4 way or 2 way
	446 series – 4 way or 2 way
	448 series – 2 way
Light duty:	443 series – 4 way or 2 way
	444 series – 4 way or 2 way

Glass Connections:

Fixed	M8 CSK
	M8 CSK Disc
	M10 CSK
	M10 CSK Disc
Swivel	60/22-22n to suit up to 22mm total glass thickness
	60/22-42n to suit up to 42mm total glass thickness

Material and Finish

All fittings are 316 marine grade stainless steel and available in satin and polished finish.

Installation

The SpiderFit range can be used with Metro GlassTech TempaFloat, TempaSoak, TempaScreen or TempaPrint Toughened Safety Glass (TSG) or SafeLite Toughened Laminated Safety Glass (TLSG)

Benefits

- Tested by independent testing facility under static and dynamic loadings
- Suitable for 8mm to 19mm TSG
- Suitable for 11.5mm to 22mm TLSG
- Can be used with point fixed IGUs, up to maximum 42mm thick
- Good corrosion resistance



Austvision 446/4M heavy duty spider fitting



Austvision M10 CSK Disc Fixed Connector



Austvision 60/22-22n swivel connector

MFG is a Division of