

Austvision

Version 1

SpiderLink

Glass Balustrade Connector

The Austvision SpiderLink are light duty Spider Fittings designed primarily for balustrade infill panels, pool fences and internal glass screens connected to posts and balusters.

The SpiderLink uses simple techniques for connecting Toughened Safety Glass panels to a post or frame by means of clamps or point fixings.

Types

The SpiderLink is available with 2 fixing options;

443 series – 4 or 2 way spider with a central M10 fixing

444 series – 4 or 2 way spider with slotted M6 clamp fixing

Glass fixings can be stepped or countersunk disc to suit the application and glass thickness

Material and Finish

All fittings are cast 316 marine grade stainless steel in satin and polished finish.

Installation

The SpiderLink can be used with Metro GlassTech TempaFloat, TempaSoak, TempaScreen or TempaPrint Toughened Safety Glass (TSG) or SafeLite Toughened Laminated Safety Glass (TLSG)

Benefits

- Easy to measure and install
- Mechanical strength tested
- Adjustable
- Suitable for 8mm toughened to 20mm laminated glass
- Good corrosion resistance
- Range of fitting configurations to suit applications

Compliance

The SpiderLink can be used in conjunction with glass panels selected from the GANZ Balustrade Design Tables in accordance with design loads selected from AS/NZS 1170, and applied in accordance with B1/VM1.

MFG is a Division of